

PackLocity® 16/22

Heavy duty shrink system for **quick** and consistent high-volume production...



SPECIFICATIONS

Film capacity: 22" wide (508mm)

L-Bar seal area: 16"W x 22"L

Machine dim: 94"L x 46"W x 61"H

Tunnel chamber: 24"L x 18"W x 9"H

Electrical: 220V, 3Ph, 20 Amp

Weight: 485 lbs

Max. product height: 8"

Conveyor speed: 1-25 PPM

STANDARD FEATURES & BENEFITS

- * Automatic motorized L-Bar seal jaw with adjustable seal timer
- * Production Speed: up to 16 to 20 packages per minute
- * Seal area: 16" x 22"
- * Seal temperature controller provides consistency of seal performance
- * Power take away conveyor
- * Seal dwell control provides additional flexibility for utilizing a wide range of films
- * Easy-to-use operator controls for fast set-up
- * Quick adjustments facilitate the centering of the seal on the product
- * Adjustable airflow and variable tunnel conveyor speed to enhance shrink performance
- * Automatic cool down cycle extends the life of the system
- * Adjustable product tray and film cradle with pinwheel perforators
- * Film cradle can accommodate up to 22" wide rolls of film
- * Tunnel curtain design minimizes heat loss and maintains tunnel temperature consistency
- * Robust design with a welded steel frame and heavy duty seal arm
- * 220 Volt, 3Ph, 20 Amp
- * Heavy duty stand with locking casters

PackLocity 16/22 system provides increased productivity and years of trouble free operation

Authorized Distributor:



254 W. Airport Freeway Irving, TX 75062-6322 USA
Tel: 972-438-2995 □ Fax: 972-438-2876
www.sgroup.org □ info@sgroup.org